Internal Calibration Touch Screen Analytical Balance(0.1mg)



Specification

Model	SN-FA1004T	SN-FA1104T	SN-FA1204T	SN-FA2004T	SN-FA2104T	SN-FA2204T
Capacity	100g	110g	120g	200g	210g	220g
Readability	0.0001g	0.0001g	0.0001g	0.0001g	0.0001g	0.0001g
Min Weighing	0.0004g	0.0004g	0.0004g	0.0004g	0.0004g	0.0004g
Repeatability	±0.0002g	±0.0002g	±0.0002g	±0.0002g	±0.0002g	±0.0002g
Linearity	±0.0003g	±0.0003g	±0.0003g	±0.0003g	±0.0003g	±0.0003g
Stable Time	≤3S	≤3S	≤3S	≤3S	≤3S	≤3S
Pan Size	Ø80mm	Ø80mm	Ø80mm	Ø80mm	Ø80mm	Ø80mm
Calibration	Internal Calibration					
Appearance Size	340x215x350mm					
Draft Shield Size	240x190x265mm					
RS232	Standard					
USB	Optional					
Printer	Optional					
Temperature	15-35℃					
Cal. Weight	100g	100g	100g	200g	200g	200g
Packing Size	475x315x485mm					
Gross Weight	11kg					

Features

Internal autocalibration
5 Inch touch panel
One key/Time trigger internal calibration
Electromagnetic force sensor
Aluminum shell/Large space wind proof cover
Tare function/Counting/Density/Percentage
Unit conversion(g/mg/ct/oz) ...
Under weighing
Sensitivity/Speed set
Overload alarm/Fault alarm/Level indicator
Option: Density kit (Solid/Liquid)